

AOS01 + COPPO

ANCHOR POINT FOR ROOFS WITH FAUX TILES

FAST

Easy installation because it is configured as a single plate.

COMPLETE

The package includes fasteners and cellular rubber seals, to ensure water-proofing.




LOAD DIRECTION



TYPES OF APPLICATION



INCLUDED IN THE PACKAGE



TECHNICAL DATA*

substructure	minimum thickness	fastening systems included	substructure	minimum thickness	fastening systems included
Fe	0,5 mm	rivet 6,3 x 20,2 mm with EPDM washer (x 24)	Al	0,7 mm	rivet 6,3 x 20,2 mm with EPDM washer (x 24)

* The values indicated are the result of experimental tests carried out under the supervision of third parties in accordance with the standard referred to. For a calculation report with minimum distances according to the relevant standard requirements, the substructure must be checked by a qualified engineer before installation.

COPPO | CODES AND DIMENSIONS

A2
AISI 304

CODE	material	B [mm]	H [mm]	L [mm]	pcs	
COPPO	AISI 304 stainless steel grade 1.4301	420	65	322	1	
AOS01	AISI 304 stainless steel grade 1.4301	60	-	98	1	
RIV6320	rivets 6,3 x 20,2 mm with EPDM washer	-	-	-	33	